



EMCO VCCU EE-402

Features :

- Independent settings for Lower, Raise, Undervoltage and Overvoltage
- Variable Time Delay settings
- LED indications for Raise, Lower and Time delay operations
- Projection mounting

Technical Specifications

Auxiliary Supply	: 230V AC \pm 10%, 50Hz, 5VA	Output contacts	: 1 pair of NO contacts each for Raise and Lower with 5A @ 240V AC or 24V DC contact rating 1 pair of C/O contacts for UV / OV with same rating
Lower Setting	: Adjustable from 200V to 250V	Operating Temp.	: 0 to 45°C
Raise Setting	: Adjustable from 200V to 250V	Overall size	: 92 x 92 x 120 mm (H x W x D)
Undervoltage Setting	: Adjustable from 180V to 230V	Mounting	: 122 x 62 mm (H x W)
Overvoltage Setting	: Adjustable from 220V to 260V	Weight	: 2Kg approx.
Time delay setting	: Adjustable from 0.5 to 10 sec.		

Product specifications are subject to change without notice.

EMCO ELECTRONICS

(An ISO 9001:2008 Mfg. Co.)



H.O. : 302, Vasan Udyog Bhavan, Senapati Bapat Marg, Opp. Phoenix mill, Lower Parel (W), Mumbai-400013.
 ■Tel.: +91-22-2490 2283 / 2492 3183. ■Fax : +91-22-2495 1024. ■E-mail : office@emcoelectronics.org

Factory : 13, Kedarnath, Tungreshwar Indl. Complex No. 1, Satali, Vasai (E), Dist - Thane. 401 208.
 ■Tel.: +91-250-2481 783 / 804, +91-250-6480 114 ■Fax : +91-250-2481 087.
 ■E-mail : mumbai@emcoelectronics.org

South : 15, Wood Street, (1st floor), Richmond Road, Bangalore – 560 025.
 ■Tel.: +91-80-2557 0215. ■Fax : +91-80-2556 6066. ■E-mail : emcoblrl@bgl.vsnl.net.in

